

HELUCONTROL® BS-SY-JB



PVC single core, Multi-Norm switchgear & control panel wires



TECHNICAL DATA

Special PVC control cable with reference to DIN VDE 0285-525-2-51 / DIN EN 50525-2-51

Temperature range	flexible -15°C to +70°C fixed -40°C to +80°C
Nominal voltage	AC U ₀ /U 300/500 V
Test voltage core/core	2000 V
Breakdown voltage	4000 V
Minimum bending radius	flexible 20x Outer-Ø fixed 7,5x Outer-Ø

CABLE STRUCTURE

- Bare copper conductor to DIN VDE 0295 cl. 5, fine wire, BS 6360 cl. 5, IEC 60228 cl. 5
- Core insulation of special PVC in reference to EN 50363-3 T12
- Coloured cores according to HD 308 S2
- GN-YE conductor, 3 cores and above in the outer layer
- Cores stranded together in layers with optimal lay length
- Inner sheath special PVC in reference to EN 50363-4-1 TM2
- Galvanized steel wire braid
- Outer sheath of special PVC compound in reference to EN 50363-4-1 TM2
- Outer sheath transparent
- With meter marking

PROPERTIES

- Good oil and chemical resistance
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

TESTS

- Flame retardant according to DIN 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2
- CPR-class: Eca

APPLICATION

BS-SY-JB Cables are used as interconnections for power and control applications within the following industries and applications: machine tool industry, plant installations, power stations and in data equipment.

NOTES

- G = with green/yellow conductor

X = without green/yellow conductor (OB)

- Cables can also be delivered with numbered cores as BS-SY-JZ

Part no.	No. cores x cross-sec. mm ²	Outer Ø mm, approx.	Weight kg/ km, approx.
11001218	2 x 0,75	7,2	72
11001219	3 G 0,75	7,6	82
11001220	4 G 0,75	8,1	98
11001221	5 G 0,75	8,8	112
11001222	7 G 0,75	9,4	139
11001224	12 G 0,75	11,9	228
11001226	18 G 0,75	13,8	312
11001228	25 G 0,75	16,3	436
11001230	34 G 0,75	18,1	556
11001236	2 x 1	7,7	83
11001237	3 G 1	8,1	97
11001238	4 G 1	8,7	115
11001239	5 G 1	9,4	132
11001240	7 G 1	10,1	166
11001242	12 G 1	12,9	274
11001244	18 G 1	14,9	379
11001246	25 G 1	17,7	531
11001247	34 G 1	19,7	679
11001253	2 x 1,5	8,4	102
11001254	3 G 1,5	8,8	119
11001255	4 G 1,5	9,5	145
11001256	5 G 1,5	10,4	166
11001257	7 G 1,5	11,1	200
11001259	12 G 1,5	14,3	354
11001261	18 G 1,5	16,6	495

Part no.	No. cores x cross-sec. mm ²	Outer Ø mm, approx.	Weight kg/ km, approx.
11001263	25 G 1,5	19,8	696
11001264	34 G 1,5	22,1	894
11001270	2 x 2,5	9,5	138
11001271	3 G 2,5	10	165
11001272	4 G 2,5	10,9	203
11001273	5 G 2,5	11,9	234
11001274	7 G 2,5	12,8	301
11001276	12 G 2,5	16,7	512
11001278	18 G 2,5	19,5	723
11001280	25 G 2,5	23,3	1023
11001281	34 G 2,5	26,1	1327
11001285	2 x 4	11,1	199
11001286	3 G 4	11,8	243
11001287	4 G 4	12,9	300
11001288	5 G 4	14,1	344
11001289	7 G 4	15,2	458
11001290	2 x 6	12,7	271
11001291	3 G 6	13,5	332
11001292	4 G 6	14,8	416
11001293	5 G 6	16,3	481
11001295	2 x 10	15,5	414
11001296	3 G 10	16,4	524
11001297	4 G 10	18,1	658
11001298	5 G 10	20	766
11001300	2 x 16	18,5	600

HELUCONTROL® BS-SY-JB



PVC single core, Multi-Norm switchgear & control panel wires

Part no.	No.cores x cross- sec. mm ²	Outer Ø mm, approx.	Weight kg/ km, approx.
11001301	3 G 16	19,6	689
11001302	4 G 16	21,7	887
11001303	5 G 16	24,1	1118
11001305	3 G 25	23,8	1019
11001306	4 G 25	26,4	1321
11001307	5 G 25	29,4	1674
11001308	3 G 35	27,7	1558

Part no.	No.cores x cross- sec. mm ²	Outer Ø mm, approx.	Weight kg/ km, approx.
11001309	4 G 35	30,9	1983
11001310	5 G 35	34,3	2467
11001311	3 G 50	33,4	2253
11001312	4 G 50	37,9	3018
11001314	3 G 70	38,3	3095
11001315	4 G 70	42,8	3976