


Fibre Optic Cable flexible

WK - UL/CSA

HELUCOM® WK

A-V(ZN)YY



Cable structure

Core type: Tight buffer
Strain relief elements: Aramide
Outer sheath colour: Orange

Temperature range

Laying, min.: 0°C
Laying, max.: +50°C
Operating, min.: -30°C
Operating, max.: +80°C

Other data

Max. tensile force: 1200 N
Max. transverse pressure: 500 N / cm
Longitudinally water-tight acc. to IEC 60794-1-2-F5
Applicable UL standards: OFNG UL 1685
Applicable CSA standards: FT4
UV-resistant
Bending cycles acc. to IEC 60794-1-2-E6: 9.000
Oil-resistant

Designation	Number of fibres	Fibre type	Fibre category	Outer Ø app. mm	Outer sheath material	Inner sheath material	Min. stat. bending radius mm	Flame proof	halogen-free	UL	Weight kg / km	Part no.
Fibre-optic cable	4	Multimode G50/125	OM2	7,0	PVC	PVC	75	yes	no	yes	50	802792
Fibre-optic cable	4	Multimode G62.5/125	OM1	7,0	PVC	PVC	75	yes	no	yes	50	803934
Fibre-optic cable	4	Single-mode E9/125	ITU-T G.652d	7,0	PVC	PVC	75	yes	no	yes	50	803935

Dimensions and specifications may be changed without prior notice.

Application

These HELUCOM® cables were designed as mobile field cables. They are easily wound up on a drum and are very tension-proof. As the outer sheath is tightly anchored on the aramid braiding, it is especially suitable for mobile use. The advantage of these cables is obvious especially where mobile fibre-optic lines have to be installed, such as windturbine projects, TV transmission, supervision of protected areas, etc. This series with PVC jacket is certified according to the **UL/CSA standard OFNG/ FT4**.