

HELUKAT® 600T CAT.7 SF/FTP PUR TORSION

CC-Link IE Field certified



TECHNICAL DATA

Industrial Ethernet cable / Cat. 7 acc. to ISO/IEC 11801, DIN EN 50173, IEC 61156-6, DIN EN 50288-4-2, UL-Std. 444 (CMX), CSA-Std. C22.2 No. 214 - CMX, UL-Std. 758 (AWM) Style 20940

Temperature range	flexible -30°C to +70°C fixed installation -40°C to +80°C UL (CMX) to +75°C UL (AWM) to +80°C
Peak operating voltage	125 V (not for high power current installation purposes)
Test voltage core/core	750 V
Conductor resistance at 20°C	max. 87.6 Ohm/km
Loop resistance at 20°C	max. 175.2 Ohm/km
Insulation resistance	min. 5.0 GOhm x km
Mutual capacitance core/core	at 800 Hz, approx. 45 pF/m
Rel. Velocity of Propagation	approx. 77%
Characteristic impedance	at 1 to 100 MHz, 100 Ohm ± 15 Ohm at 101 to 600 MHz, 100 Ohm ± 20 Ohm
Caloric load	approx. 0.80 MJ/m
Minimum bending radius	flexible 15x Outer-Ø fixed installation 8x Outer-Ø

CABLE STRUCTURE

- Copper wire tinned, AWG sizes
- Core insulation: Foam PE
- Core identification: colour coded, pairs:
 - No. 1: white / blue
 - No. 2: white / orange
 - No. 3: white / green
 - No. 4: white / brown
- Cores stranded in pairs with optimal lay lengths

- Screening element: pairs, plastic-coated aluminium foil (St)
- Pairs with optimal lay lengths stranded around a central cross-shaped filler
- 1. Screen: metallised conductive fleece
- 2. Screen: braided screen of tinned copper wires
- Outer sheath: PUR
- Sheath colour: green
- Length marking: in metres

PROPERTIES

- resistant to: oil, UV radiation, hydrolysis, microbes, coolants, greases
- abrasion-resistant, tear-resistant, cut-resistant, wear-resistant, low adhesion
- torsion rated
- halogen-free
- flame-retardant

TESTS

- halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1
- flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2

APPLICATION

HELUKAT® 600T CAT.7 SF/FTP PUR TORSION Cable is designed for use in robots. It provides excellent transmission characteristics under extremely difficult conditions.

NOTES

- Conductor sizes are based on the AWG measurement system, metric conductor sizes (mm²) are approximated and are for reference only
- UL Voltage Rating: 600 V

TYPICAL VALUES

Frequency (MHz)	10	16	62.5	100	200	300	600
Attenuation (dB/100m)	7.0	9.0	17.5	22.5	36.0	50.0	58.5
NEXT (dB)	100.0	100.0	100.0	100.0	97.0	90.0	89.0
ACR (dB/100m)	93.0	91.0	82.5	77.5	61.0	40.0	30.5

Part no.	No. cores x AWG-No.	Cross-sec. mm ² , approx.	Conductor Ø mm, approx.	Core Ø mm, approx.	Outer Ø mm, approx.	Cu-weight kg/km	Weight kg/km, approx.
805828	4 x 2 x AWG 24 /7	0.22	0.6	1.3	8.7	46.0	95.0