

# Certificate of compliance

with the order 2.1 according to EN 10 204

## H03VV-F / 03VV-F

We confirm that the above mentioned **PVC connection cable** is produced ,  
**2 - 4 core(s): acc. to DIN VDE 0285-525-2-11 / DIN EN 50525-2-11;**  
**5 - 7 core(s): in alignment with DIN VDE 0285-525-2-11 / DIN EN 50525-2-11** and tested according to DIN EN 50395, DIN EN 50396.

## TECHNICAL DATA

**Temperature range** flexible -5°C to +70°C  
fixed -40°C to +70°C  
**Nominal voltage** AC U<sub>0</sub>/U 300/300 V

## TESTS

flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2  
certifications and approvals:  
H03VV-F: HAR  
H03VV-F: EAC

## PROPERTIES

the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers



Product conforms with Low-Voltage Directive 2014/35/EU

**HELU KABEL GmbH**  
Technical Department

This document is valid without signature

**Date of issue**  
19.12.2024

**Date of expiration**  
31.12.2026

**Point of Contact**  
Christian Dettmer  
Tel. +49 7150 9209-712  
techsupport@helukabel.de  
helukabel.com

**HELU KABEL GmbH**  
Headquarters  
Schloßhaldenstr. 10  
71282 Hemmingen  
Germany