

# Certificate of compliance

with the order 2.1 according to EN 10 204

## H01N2-E

We confirm that the above mentioned **Arc welding cable** is produced **acc. to DIN VDE 0285-525-2-81 / DIN EN 50525-2-81** and tested according to DIN EN 50395, DIN EN 50396.

### TECHNICAL DATA

<b>Temperature range</b>	flexible -20°C to +85°C fixed -35°C to +85°C
<b>Permissible operating temperature of the conductor</b>	+85°C
<b>Nominal voltage</b>	AC U <sub>0</sub> /U 100/100 V

### TESTS

flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2

oil-resistant acc. to DIN VDE 0473-811-404 / DIN EN 60811-404 / IEC 60811-404

certifications and approvals:

HAR

EAC

### PROPERTIES

the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers



Product conforms with Low-Voltage Directive 2014/35/EU

**HELU KABEL GmbH**  
Technical Department

This document is valid without signature

**Date of issue**  
17.02.2025

**Date of expiration**  
31.12.2027

**Point of Contact**  
Christian Dettmer  
Tel. +49 7150 9209-712  
techsupport@helukabel.de  
helukabel.com

**HELU KABEL GmbH**  
Headquarters  
Schloßhaldenstrasse 10  
71282 Hemmingen  
Germany