

Certificate of compliance

with the order 2.1 according to EN 10 204

SIFF

We confirm that the above mentioned **Silicone single core** is produced **in alignment with DIN VDE 0250-1, DIN VDE 0250-502** and tested according to DIN EN 50395, DIN EN 50396.

TECHNICAL DATA

Temperature range

flexible -25°C to +180°C

fixed -60°C to +180°C

Permissible operating temperature of the conductor

+180°C

Nominal voltage

AC U₀/U 300/500 V

TESTS

halogen-free acc. to DIN VDE 0482-754-1 / DIN EN 60754-1 / IEC 60754-1

corrosiveness of combustion gases acc. to DIN VDE 0482-754-2 / DIN EN 60754-2 / IEC 60754-2

flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2

certifications and approvals:

EAC



Product conforms with Low-Voltage Directive 2014/35/EU

HELU KABEL GmbH
Technical Department

This document is valid without signature

Date of issue
17.03.2025

Date of expiration
31.12.2027

Point of Contact
Christian Dettmer
Tel. +49 7150 9209-712
techsupport@helukabel.de
helukabel.com

HELU KABEL GmbH
Headquarters
Schloßhaldenstraße 10
71282 Hemmingen
Germany