

Certificate of compliance

with the order 2.1 according to EN 10 204

TRAYCONTROL® 300-C TP

TECHNICAL DATA

Temperature range	flexible +5°C to +50°C fixed -25°C to +105°C
Nominal voltage	AC U 300 V

TESTS

flame-retardant acc. to CSA FT4
oil-resistant acc. to UL Std 13 No. 40, Oil Res I / Oil Res II
Cold Bend Test acc. to UL Std. 13 No. 22
Impact Test (-ER) acc. to UL Std. 13 No. 23
Crushing Test (-ER) acc. to UL Std. 13 No. 24
Vertical-Tray Flame Test (FT4) CSA-Std. C22.2 No. 2256
certifications and approvals:
EAC
ECOLAB®

PROPERTIES

the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers



Product conforms with Low-Voltage Directive 2014/35/EU

HELU KABEL GmbH
Technical Department

This document is valid without signature

Date of issue
13.08.2025

Date of expiration
31.12.2027

Point of Contact
Christian Dettmer
Tel. +49 7150 9209-712
techsupport@helukabel.de
helukabel.com

HELU KABEL GmbH
Headquarters
Schloßhaldenstrasse 10
71282 Hemmingen
Germany