

# Certificate of compliance

with the order 2.1 according to EN 10 204

## PAAR-TRONIC

We confirm that the above mentioned **PVC data cable** is produced **in alignment with DIN VDE 0812** and tested according to DIN EN 50395, DIN EN 50396.

## TECHNICAL DATA

|                               |                                                          |
|-------------------------------|----------------------------------------------------------|
| <b>Temperature range</b>      | flexible -5°C to +80°C<br>fixed -30°C to +80°C           |
| <b>Peak operating voltage</b> | 350 V (not for high power current installation purposes) |

## TESTS

flame-retardant acc. to DIN VDE 0482-332-1-2 / DIN EN 60332-1-2 / IEC 60332-1-2  
certifications and approvals:  
EAC

## PROPERTIES

the materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers



Product conforms with Low-Voltage Directive 2014/35/EU

**HELUX KABEL GmbH**  
Technical Department

This document is valid without signature

**Date of issue**  
26.03.2026

**Date of expiration**  
31.12.2028

**Point of Contact**  
Christian Dettmer  
Tel. +49 7150 9209-712  
techsupport@helukabel.de  
helu.com

**HELUX KABEL GmbH**  
Headquarters  
Schloßhaldenstrasse 10  
71282 Hemmingen  
Germany